

SALES, SPARE & SERVICE









Mfg. - All Type of Pouch Packing Machine, F.F.S. Machine, Collar Types Machines, Semi Pnumatic Machine

FFS All Size Machine

Product Pan Masala, Gutkha, Tea, Pulses, Granules, Spices,

Type of Seal Centre Seal

Packing material Heat Sealable Laminated Film

Filling Range 0.5 gm to 500 gm

(depend on the nature of product)

Size of bag / pouch W 30 mm to 200 mm,

L-30 mm to 300 mm

Production Output 30 to 50 bag /minute

(Depend on the nature of product)

Power Consumption 2 Kw, Motor 0.5 HP / 220V single phase

Filling System Fix cup & adjustable cup

Machine Size L 750mm, @ W 550 mm, H 1800 mm (Approx.)

Machine Weight 250 Kgs

Filling Accuracy $\pm 1\%$



Model No. AP 101-104

FFS All Size Machine

Product Shampoo, Lubricant, Oil, Wine, Paste etc.

Type of Seal Center Seal

Packing material Heat Sealable Laminated Film

Filling Range 5gm to 200 gm

Size of bag / pouch W 40 mm to 180 mm,

L-50 mm to 200 mm

Production Output 20 to 60 Pouch /minute

(Depends on nature of product)

Power Consumption 2 Kw, Motor 1/2 HP / 220V single phase

Filling System Volumetric Piston Filling

Machine Size L 750mm, W 550 mm, H 1500 mm (Apprx.)

Machine Weight 250 Kgs (Apprx.)

Filling Accuracy $\pm 1\%$



Model No.

AP 101-104

Semi Pneumatic Cup Filler Machine

Packing Material Heat Sealable Laminated Films

Roll Width Max. - 380 mm, Min. 100 mm

Pouch Type Center Seal Pouch

Pouch Dimension Width = so 380 mm, Height = 65 *300 mm

Electrical Supply 230 V / A.C / Single Phase / 50 Hz

Power Consumption 3 Kw

Compressed Air Required 6 CFM @ 6 Bar

Production Rate 30 Shots Per Minute (Varies as per the Nature of

Product & Filling Range)

Weight Approx. Weight 250 Kgs.

Machine Dimension H 2150 mm W - 680 L 900 mm



Model No.

Semi Pneumatic Auger Filler Machine

Products Adjustable Augar Filling

Filling Accuracy +1 to 1.5% Depend Upon Nature of Product

Type of Seal Three Side / Four Side, Center or Back Seal

Filling Range 15 gm upto 500 gm. (as per req.)

Packing Material Sticky Powder

Size of Bag I Pouch W-100 to 160 mm, L-80 to 130 mm

Speedy Capacity 30 to 50 PPM

Machine Dimension H 2150 mm, W 680 mm, L 900 mm

Wooden Case H 1700 mm

Dimension W 1000 mm, L 1100 mm

Film Roll Dimension OD 250 to 300 mm max, ID 75 mm min

Power Consumption Motor 1/2 H.P Single Phase 1 Nos,

1 HP. Three Phase 2 Nos, 3 Phase supply

Filling Mechanism Clutch & Break Gear Box

Heater Clutch & Break Controller, 150 x 2 + 300 x 2



Pneumatic Collar Type Machine PLC Based

Products Powder (Free Flowing & Sticky)

Filling System Voloumatric

Filling Accuracy $\pm 1\%$ (Depend on nature of product)

Type of Seal Centre Seal & Back Seal

Filling Range 25 gm upto 2000 gms.

(Depend on nature of product)

Packing Material Heat Sealable Laminated Films

Pouch Dimensions 100-460 mm

Power Consumption 3.5 Kw, 3 Phase

Compressed Air Required 6 CFM@6 Bar (3 HP. Compressor)

Production Output 20-50 pouches per minute

(Depend on nature & quantity of product

Weight 650 Kg (Apprx.)

Machine Size (Bager Size) L:1830 mm, W:1270 mm, H: 2600 mm (Apprx.)



Pneumatic Collar Type Auger Filler Machine PLC Based with Screw Conveyor

Products Powder (Free Flowing & Sticky)

Filling System Servo Aughar

Filling Accuracy $\pm 1\%$ (Depend on nature of product)

Type of Seal Centre Seal & Back Seal

Filling Range 25 gm upto 2000 gms.

(Depend on nature of product)

Packing Material Heat Sealable Laminated Films

Pouch Dimensions 100-460 mm

Power Consumption 5.5 Kw, 3 Phase

Compressed Air Required 6 CFM@6 Bar (3 HP. Compressor)

Production Output 20-50 pouches per minute

(Depend on nature & quantity of product

Weight 650 Kg (Apprx.)+150 Kg (Screw conveyor)

Machine Size (Bager Size) L:1830 mm, W:1270 mm, H: 2600 mm (Apprx.)



Horizontal Flow Wrapper Machine

Product Cake, Biscuit, Automobile parts, any type of single product

Feeding Style Automatic / Manual

Packing Style Center Seal

Packing Size Length: 50 mm to 400 mm

Width: 30 mm to 180 mm

Packing Material Heat Sealable Laminated Films

Production Output Approx. 40 to 120. Pouch / Minutes

(Depend upon the Packing size)

Power Required Load: 3Kw, Single Phase

Machine Dimensions Approx 1080 x 1700 x 1800 mm

Weight Approx. 700 Kgs.



Pneumatic Collar Type Machine with Multihead load Cell

Products Granules

Weigh Head Nos. 10 Head, 14 Head Packing

Type of Seal Centre Seal or Back Seal

Packing Material Heat Sealable Laminated Film

Filling Range 5 gm upto 2000 gms (Depend on nature of product)

Power Consumption 4 Kw

Compressed Air 13 CFM@6 Bar (5 H. P. Compressor)

Production Output 20-70 pouches/minute

(Depend on nature & quantity of product)

Touch Screen 10.4" Colour Display

with Touch Screen

Material of Chasis 304 Stainless Steel

Thickness of Bucket 1.2mm plain S.S. 304

Weight 1550 Kg (Apprx.) with Z Allivator

Machine Size L 2900 mm, W 2100mm, H 3660mm (Apprx.)









Model No. AP 104



Model No. AP 105







Model No. AP 202



Model No. AP 203



Model No. AP 204



Model No. AP 301



Model No. AP 301



Model No. AP 302

Model No. AP 401



Model No. AP 501



Model No. AP 502



Model No. AP 504



Model No. AP 503



0, Arohi Packaging, Gram Chhapora, Dharsiva, Raipur 493221 (C.G.)

Mob.: 78696 08514 | Email: arohipackaging@gmail.com | Web: www.arohipackaging.com